

TECHNICAL DATA SHEET

INTEGRAL S1P SRC

Safety shoes

Article NO:	G1028
Upper:	buffalo leather
Liner:	non-woven fabric, foam
Sole:	PU/TPU
Description:	full-leather high shoes steel toecap and midplate
Size:	39 - 48



PU/TPU sole is antiwriting, resistant to oils, fuels and contact heat up to 110°C. It is antistatic and absorbs shocks up to 20 J in the heel area. This shoes are suitable for use at heavy machinery.

Type and degree of protection:

Category	EN ISO 20345
Antistatic properties	x
Absorption of energy in the heel area	x
Sole with pattern- oil resistance	x
Safety toecap for toe protection	x
Puncture resistance (protective insole)	x
Slip resistant ceramic tile floor with SLS and on steel floor with glycerol (SRC)	x



This personal protective equipment is in conformity with this harmonized European Standard:

EN ISO 20345:2011 : Personal protective equipment - safety shoes.

Certified by notified body no. 0362 (ITS Testing Services),
Certificate number LEC F100372831 (dated 21st January 2019).

Pairs in carton:	10
Carton weight:	17,3 kg
Carton size:	0,090 m ³



The shoes have to be perfect as for form and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be included (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.
