



**ARDON**<sup>®</sup>  
**WORKWEAR**  
**& OUTDOOR**

# ARDON<sup>®</sup> LEADERWIN S3

SAFETY SHOES



TECHNICAL SHEET



**DEFUSE  
CONTROL**



**WINTER**



**WATER  
REPELLENT**



**REFLECTIVE**



**NONMETALLIC**



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

# ARDON<sup>®</sup> LEADERWIN S3

SAFETY SHOES

**ARTICLE** G3393

**MATERIAL**

Upper NUBUCK cowhide leather, thickness 1.8 - 2 mm, hydrophobic /fabric  
 Lining Synthetic fur  
 Sole PU/PU, direct injection  
 Toe cap Fibreglass 459  
 Plate Kevlar  
 Insole BASIC - synthetic fur

**SIZE** 38-48

**UNIT** pair

**PACKAGE**

Units in a carton 10 pairs  
 Units in a box 1 pair

**DIMENSIONS**

	38-42	43-48	
Carton H x W x D (cm)	34 x 48 x 65	37 x 50 x 69	
Carton (cbm)	0,106	0,128	



TECHNICAL SHEET

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	-	-	252	259	266	272	278	286	291	298	306	312	319	-	-	-
Foot length cm	-	-	-	24,2	24,9	25,6	26,2	26,8	27,6	28,1	28,8	29,6	30,2	30,9	-	-	-

**DESCRIPTION**

Safety shoes with an upper made of high-quality NUBUCK leather, hydrophobic and fabric, with a fiberglass toe cap and Kevlar insole, reflective strip for higher visibility, dual-density polyurethane sole, insulation with synthetic fur.



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment - Safety footwear

Category: S3 CI SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
insulation of the bottom of the shoe against heat		
insulation of the bottom of the shoe against the cold	✓	
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



**ARDON®**

**WORKWEAR  
& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G3393/38	8592390168474	16,1	1,610
G3393/39	8592390168481	16,5	1,650
G3393/40	8592390168498	17,5	1,750
G3393/41	8592390168504	17,6	1,760
G3393/42	8592390168511	17,8	1,780
G3393/43	8592390168528	18,0	1,800
G3393/44	8592390168535	18,5	1,850
G3393/45	8592390168542	19,0	1,900
G3393/46	8592390168559	20,8	2,080
G3393/47	8592390168566	21,5	2,150
G3393/48	8592390168573	22,0	2,200





**ARDON®**

**WORKWEAR  
& OUTDOOR**





**ARDON®**

**WORKWEAR  
& OUTDOOR**



TECHNICAL SHEET