



ARDON®
WORKWEAR
& OUTDOOR

ARDON® DIGGER S1

SAFETY SHOES



TECHNICAL SHEET



DRY AIR



DEFUSE CONTROL



NONMETALLIC



REFLECTIVE



ARDON[®]
WORKWEAR
 & **OUTDOOR**

ARDON[®] DIGGER S1

SAFETY SHOES

ARTICLE G3238

MATERIAL

Upper MICROFIBER / CANVAS type fabrics
 Lining MESH laminated breathable fabric
 Sole MD/rubber/TPU, glued technology
 Toe cap composite 885
 Plate -
 Insole ANATOMIC FOAM anatomically shaped EVA foam

SIZE

39-46

UNIT

pair

PACKAGE

Units in a carton 10 pairs

Units in a box 1 pair

DIMENSIONS

Carton H x W x D (cm)

39-43	44-46
34 x 48.5 x 63	37 x 52.5 x 63

Carton (cbm)

0,104	0,122
-------	-------

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-				258	264	271	278	284	291	298	304			-	-	-
Foot length cm	-				25,3	25,9	26,6	27,3	27,9	28,6	29,3	29,9			-	-	-

DESCRIPTION

Low shoes in sports design. Breathable upper is made of solid fabric and microfiber, the toe cap is reinforced with PU. Wearing comfort is increased by padding the tongue and the area around the heel and ankle, but mainly the shoes are equipped with an anatomically shaped insole, made of a material that effectively dampens the impact of the tread and ensures comfort even during long-term wear. The sole made of a combination of MD / rubber / TPU material ensures a soft tread and at the same time provides the highest level of anti-slip properties.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S1 SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)		
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



ARDON®

**WORKWEAR
& OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3238/39	8592390094995	12.00	1.200
G3238/40	8592390095008	12.10	1.210
G3238/41	8592390095015	12.30	1.230
G3238/42	8592390095022	12.50	1.250
G3238/43	8592390095039	12.80	1.280
G3238/44	8592390095046	13.00	1.300
G3238/45	8592390095053	13.50	1.350
G3238/46	8592390095060	14.00	1.400





ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET