



ARDON®
WORKWEAR
& OUTDOOR

ARDON® GRINDLOW S1P

SAFETY SHOES



DRY AIR



**DEFUSE
CONTROL**

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

ARDON[®] GRINDLOW S1P

SAFETY SHOES

ARTICLE G3163

MATERIAL

Upper ACTION NUBUK – cowhide leather with polyurethane / fabric coating
 Lining MESH laminated breathable fabric
 Sole PU/rubber, two-component spray coating, oil resistant, anti-static, antislip, resistant up to 300 °C
 Toe cap composite 604
 Plate kevlar
 Insole ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

SIZE

UNIT

PACKAGE

Units in a carton 10 pairs
 Units in a box 1 pair

DIMENSIONS

	36-39	40-43	44-48
Carton H x W x D (cm)	31.5 x 41.5 x 61.5	33.5 x 43.5 x 61.5	37 x 43.5 x 64
Carton (cbm)	0,0804	0,0896	0,103

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	237	243	250	257	263	270	277	283	290	297	303	310	317	-	-	-
Foot length cm	-	23,2	23,8	24,5	25,2	25,8	26,5	27,2	27,8	28,5	29,2	29,8	30,5	31,2	-	-	-

DESCRIPTION

Safety low shoes with upper made of ACTIONNUBUK material - cowhide leather with polyurethane coating. The wide PU / rubber sole has SRC anti-slip properties and is resistant to contact heat up to 300 ° C. The ANATOMIC FOAM insole ensures increased comfort of the shoes. The shoes are equipped with a composite toe and a flexible Kevlar insole against punctures.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S1P HRO SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C	✓	
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3163/36	8592390068859	12.60	1.260
G3163/37	8592390068866	13.00	1.300
G3163/38	8592390068873	13.40	1.340
G3163/39	8592390068880	13.80	1.380
G3163/40	8592390068897	14.45	1.445
G3163/41	8592390068903	15.10	1.510
G3163/42	8592390068910	15.60	1.560
G3163/43	8592390068927	15.90	1.590
G3163/44	8592390068934	16.30	1.630
G3163/45	8592390068941	16.80	1.680
G3163/46	8592390068958	17.60	1.760
G3163/47	8592390068965	18.00	1.800
G3163/48	8592390068972	18.45	1.845





ARDON®
WORKWEAR
& OUTDOOR





ARDON[®]
WORKWEAR
& **OUTDOOR**



TECHNICAL SHEET