



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® DOZERLOW S3

SAFETY SHOES



TECHNICAL SHEET



DRY AIR



WATER  
REPELLENT



NONMETALLIC



ANTIBACTERIAL



REFLECTIVE



ESD



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

# ARDON<sup>®</sup> DOZERLOW S3

SAFETY SHOES

**ARTICLE** G3214

**MATERIAL**

Upper NUBUK- cowhide leather 1.8 - 2 mm thick, hydrophobic / textile  
 Lining MESH laminated breathable fabric  
 Sole PU/ PU Superline, dvousložkový nástřík

Toe cap fiberglass 522  
 Plate kevlar  
 Insole ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

**SIZE**

**UNIT** 36-48

**PACKAGE** pair

Units in a carton 10 pairs

Units in a box 1 pair

**DIMENSIONS**

Carton H x W x D 36-48  
 36 x 39,5 x 67,5

(cm)

Carton (cbm) 0,096

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	240	247	253	260	265	273	279	286	293	303	307	318	323	-	-	-
Foot length cm	-	23,5	24,2	24,8	25,5	26,0	26,8	27,4	28,1	28,8	29,8	30,2	31,3	31,8	-	-	-

**DESCRIPTION**

Safety footwear with an upper made of high-quality NUBUK cowhide leather and fabric, with a hydrophobic finish. For greater comfort, it is equipped with an anatomically shaped, antistatic, antibacterial, ESD insole. Safety is ensured by a fiberglass toe cap and a flexible Kevlar insole against punctures. The lightweight dual-density polyurethane sole meets SRC anti-slip requirements. The model is ESD, ie it protects against electrostatic discharge and can therefore be used in EPA areas.

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S3 SRC ESD

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



**ARDON®**

**WORKWEAR  
& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G3214/36	8592390080257	15.45	1.545
G3214/37	8592390080264	15.70	1.570
G3214/38	8592390080271	15.95	1.595
G3214/39	8592390080288	16.20	1.620
G3214/40	8592390080295	16.45	1.645
G3214/41	8592390080301	16.70	1.670
G3214/42	8592390080318	16.95	1.695
G3214/43	8592390080325	17.20	1.720
G3214/44	8592390080332	17.45	1.745
G3214/45	8592390080349	17.70	1.770
G3214/46	8592390080356	17.95	1.795
G3214/47	8592390080363	18.20	1.820
G3214/48	8592390080370	18.45	1.845





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**

**WORKWEAR  
& OUTDOOR**



TECHNICAL SHEET