



## ARDON<sup>®</sup> DERRICK S3

SAFETY SHOES

TECHNICAL SHEET



DRY AIR



DEFUSE  
CONTROL



NONMETALLIC



WATER  
REPELLENT



FLAT ANTI-SLIP



**ARDON®**  
**WORKWEAR**  
**OUTDOOR**

# ARDON® DERRICK S3

SAFETY SHOES

**ARTICLE** G3160

## MATERIAL

Upper  
Lining  
Sole

ACTION NUBUK – cowhide leather with polyurethane / textile  
MESH laminated breathable fabric  
rubber, oil resistant, antistatic, anti-slip, glued technology

Toe cap  
Plate  
Insole

composite 459  
kevlar  
ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and  
transverse arches, absorbs shocks in the heel area

## SIZE

39-48

## UNIT

pair

## PACKAGE

Units in a carton

10 pairs

Units in a box

1 pair

## DIMENSIONS

Carton H x W x D

39-42

(cm)

32,5 x 43,5 x 59,5

43-48

Carton (cbm)

37,5 x 45,5 x 64,5

0,084

0,110

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	-	-	-	256	263	269	276	283	289	296	303	309	316	-	-	-
Foot length cm	-	-	-	-	25,1	25,8	26,4	27,1	27,8	28,4	29,1	29,8	30,4	31,1	-	-	-

## DESCRIPTION

Safety shoe in modern street design. The upper of the shoe is made of action NUBUK material with a waterproof finish, the tongue and ankle area is made of a fabric that provides higher breathability. The shoes are equipped with a composite toe and a flexible Kevlar insole against puncture. The stable flat sole made of rubber provides the highest level of anti-slip properties.

## NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S3 SRC

Categories	EN ISO 20345
E - energy absorption in the heel area	✓ 
FO - resistance to oils and fuels	✓ 
A - antistatic footwear	✓ 
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓ 
WR - upper resistant to water	✓ 
Safety toe cap for toe protection	✓ 
P - resistance to punctures (protective insole)	✓ 
SRA - slip resistance ceramic floor tiles with SLS	✓ 
HRO - resistance to contact heatup to 300 °C	✓ 
HI-insulation of the bottom of the shoe against heat	✓ 
CI-insulation of the bottom of the shoe against the cold	✓ 
Splatters of molten metal	✓ 
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓ 
The shoes do not contain metal parts	✓ 
-	
-	
-	





CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3160/39	8592390068521	13.26	1.326
G3160/40	8592390068538	13.76	1.376
G3160/41	8592390068545	14.26	1.426
G3160/42	8592390068552	14.76	1.476
G3160/43	8592390068569	16.37	1.637
G3160/44	8592390068576	16.87	1.687
G3160/45	8592390068583	17.37	1.737
G3160/46	8592390068590	17.87	1.787
G3160/47	8592390068606	18.37	1.837
G3160/48	8592390068613	18.87	1.887



**ARDON®**  
**WORKWEAR**  
**OUTDOOR**





**ARDON®**  
**WORKWEAR**  
S OUTDOOR



# TECHNICAL SHEET