



ARDON[®]
WORKWEAR
& **OUTDOOR**

ARDON[®] LEADERLOW S3

SAFETY SHOES



**DEFUSE
CONTROL**




DRY AIR



**WATER
REPELLENT**



REFLECTIVE



NONMETALLIC

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® LEADERLOW S3

SAFETY SHOES

ARTICLE

G3422

MATERIAL

Upper NUBUCK - cow leather 1,8 - 2 mm, hydrophobic / fabric
 Lining laminated breathable fabric MESH
 Sole PU/PU, two-component direct injection
 Toe cap Fibreglass 459
 Plate Kevlar
 Insole ANATOMIC FOAM – anatomically shaped from EVA foam

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton 10 pairs
 Units in a box 1 pair

DIMENSIONS

Carton H x W x D
 (cm)
 Carton (cbm)

| | 36-42 | 43-48 |
|-----------------------|--------------|--------------|
| Carton H x W x D (cm) | 34 x 48 x 65 | 37 x 50 x 69 |
| Carton (cbm) | 0,106 | 0,128 |

| Size EUR | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 | 51 |
|------------------|----|------|------|------|------|------|------|------|------|------|------|------|------|------|----|----|----|
| Insole length mm | - | 239 | 246 | 252 | 259 | 266 | 272 | 278 | 286 | 291 | 298 | 306 | 312 | 319 | - | - | - |
| Foot length cm | - | 23,4 | 24,1 | 24,7 | 25,4 | 26,1 | 26,7 | 27,3 | 28,1 | 28,6 | 29,3 | 30,1 | 30,7 | 31,4 | - | - | - |

DESCRIPTION

Safety shoes with an upper made of high-quality NUBUCK leather, hydrophobic and fabric, with a fiberglass toe cap and Kevlar insole, reflective strip for higher visibility, dual-density polyurethane sole.



ARDON[®]
WORKWEAR
& OUTDOOR

NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S3 CI SRC

| Categories | EN ISO 20345 | |
|--|--------------|--|
| E - energy absorption in the heel area | ✓ | |
| FO - resistance to oils and fuels | ✓ | |
| A - antistatic footwear | ✓ | |
| SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin | ✓ | |
| WR - upper resistant to water | ✓ | |
| Safety toe cap for toe protection | ✓ | |
| P - resistance to punctures (protective insole) | ✓ | |
| SRA - slip resistance ceramic floor tiles with SLS | | |
| HRO - resistance to contact heatup to 300 °C | | |
| HI-insulation of the bottom of the shoe against heat | | |
| CI-insulation of the bottom of the shoe against the cold | ✓ | |
| Splatters of molten metal | | |
| ESD – shoe protects against electrostatic discharge and can be used on EPA premises | | |
| The shoes do not contain metal parts | ✓ | |
| - | | |
| - | | |
| - | | |





ARDON®
WORKWEAR
& OUTDOOR

| CODE | EAN | CARTON WEIGHT (KG) | UNIT WEIGHT (KG) |
|-------------|---------------|-------------------------------|-----------------------------|
| G3422/36 | 8592390355270 | 15,0 | 1,500 |
| G3422/37 | 8592390355287 | 15,1 | 1,510 |
| G3422/38 | 8592390355294 | 15,2 | 1,520 |
| G3422/39 | 8592390355300 | 15,5 | 1,550 |
| G3422/40 | 8592390355317 | 15,8 | 1,580 |
| G3422/41 | 8592390355324 | 16,0 | 1,600 |
| G3422/42 | 8592390355331 | 16,5 | 1,650 |
| G3422/43 | 8592390355348 | 16,8 | 1,680 |
| G3422/44 | 8592390355355 | 17,0 | 1,700 |
| G3422/45 | 8592390355362 | 17,3 | 1,730 |
| G3422/46 | 8592390355379 | 17,5 | 1,750 |
| G3422/47 | 8592390355386 | 17,8 | 1,780 |
| G3422/48 | 8592390355393 | 18,0 | 1,800 |





ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

