



ARDON®
WORKWEAR
& OUTDOOR

ARDON® BRIMIC HIGH S3S ESD

SAFETY SHOES



DRY AIR



REFLECTIVE



WATER
REPELLENT



DEFUSE
CONTROL



NONMETALLIC



ESD

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® BRIMIC HIGH S3S ESD

SAFETY SHOES

ARTICLE

G3447

MATERIAL

Upper MICROFIBER synthetic fibre, 1,4 mm / TPU
Lining MESH-type laminated breathable fabric
Outsole PU/PU, two-component coating, oil resistant, antistatic, anti-slip
Toe cap Fiberglass
Plate Kevlar
Insole EVA with shock absorbing construction

SIZE

35-48

UNIT

pair

PACKAGE

Units in a carton 10 pairs
Units in a box 1 pair

DIMENSIONS

	35-42	43-48
Carton H x W x D (cm)	34 x 45,5 x 61,5	37 x 47,5 x 64
Carton (cbm)	0,0951	0,1125

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	233	240	247	253	260	267	273	280	287	293	300	307	313	320	-	-	-
Foot length cm	22,3	23,0	23,7	24,3	25,0	25,7	26,3	27,0	27,7	28,3	29,0	29,7	30,3	31,0	-	-	-

DESCRIPTION

Safety footwear with an upper made of microfiber combined with TPU. The lining is made of breathable laminated MESH fabric. The sole is made of dual-density PU applied by injection. Toe protection is provided by a fiberglass toe cap, and a Kevlar midsole protects against punctures. The insole is made of EVA with a shock-absorbing design.

TECHNICAL SHEET

NORMS

(EU) 2016/425

EN ISO 20345:2022+A1:2024

EN IEC 61340-4-3:2018

Personal protective equipment - Safety footwear
Electrostatics: Standard test methods for specific
application – Footwear

Category:

S3S SR FO ESD

Categories

EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SR - resistance to slipping on ceramic floor tiles with SLS
and on steel floors with glycerin

✓



WPA - Water penetration and absorption

✓



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



The shoes do not contain metal parts

✓



HRO - resistance to contact heatup to 300 °C



insulation of the bottom of the shoe against heat



insulation of the bottom of the shoe against the cold



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can
be used on EPA premises

✓



-

-

-



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3447/35	8592390381163	13,49	1,349
G3447/36	8592390381170	13,60	1,360
G3447/37	8592390381187	13,90	1,390
G3447/38	8592390381194	14,11	1,411
G3447/39	8592390381200	14,35	1,435
G3447/40	8592390381217	14,53	1,453
G3447/41	8592390381224	15,75	1,575
G3447/42	8592390381231	14,95	1,495
G3447/43	8592390381248	15,16	1,516
G3447/44	8592390381255	15,41	1,541
G3447/45	8592390381262	15,70	1,570
G3447/46	8592390381279	15,86	1,586
G3447/47	8592390381286	16,06	1,606
G3447/48	8592390381293	16,29	1,629



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

