



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® DIBERTIN LB S3L

SAFETY SHOES



WINTER



WATER  
 REPELLENT



REFLECTIVE

**3M**  
**Thinsulate™**  
 INSULATION



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® DIBERTIN LB S3L

SAFETY SHOES

## ARTICLE

G3452

## MATERIAL

Upper  
Lining  
Sole

cowhide leather with SPLIT LEATHER design, hydrophobic  
textile Thinsulate™ insulation  
PU/rubber, two-component spray coating, oil resistant, anti-static, antislip,  
resistant up to 300 ° C  
composite  
kevlar  
polar foam

Toe cap  
Plate  
Insole

## SIZE

## UNIT

## PACKAGE

Units in a carton  
Units in a box

37-48  
pair

10 pairs  
1 pair

## DIMENSIONS

Carton H x W x D  
(cm)  
Carton (cbm)

37-42  
66,5 x 61,5 x 33,5  
0,1370

43-48  
69 x 65,5 x 36  
0,1627

| Size EUR         | 35 | 36 | 37   | 38   | 39   | 40   | 41   | 42   | 43   | 44   | 45   | 46   | 47   | 48   | 49 | 50 | 51 |
|------------------|----|----|------|------|------|------|------|------|------|------|------|------|------|------|----|----|----|
| Insole length mm | -  | -  | 238  | 245  | 251  | 258  | 265  | 271  | 278  | 285  | 291  | 298  | 305  | 311  | -  | -  | -  |
| Foot length cm   | -  | -  | 22,8 | 23,5 | 24,1 | 24,8 | 25,5 | 26,1 | 26,8 | 27,5 | 28,1 | 28,8 | 29,5 | 30,1 | -  | -  | -  |

## DESCRIPTION

Winter mid-cut safety boots with a hydrophobic bovine leather upper. The interior Thinsulate™ lining provides reliable thermal insulation. The polar foam insole effectively protects against ground cold. Dual-density PU/rubber outsole. Equipped with non-metallic safety components.

## NORMS

(EU) 2016/425

EN ISO 20345:2022+A1 2024

Personal protective equipment –Safety footwear

Category

S3L SR FO HRO CI HI

### Categories

### EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SR - resistance to slipping on ceramic floor tiles with SLS  
and on steel floors with glycerin

✓



The shoes do not contain metal parts



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



WPA – water penetration and absorption

✓



HRO - resistance to contact heatup to 300 °C

✓



HI-insulation of the bottom of the shoe against heat

✓



CI-insulation of the bottom of the shoe against the cold

✓



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can  
be used on EPA premises



-

-

-



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

| CODE     | EAN           | CARTON WEIGHT<br>(KG) | UNIT WEIGHT<br>(KG) |
|----------|---------------|-----------------------|---------------------|
| G3452/37 | 8592390388032 | 16,10                 | 1,610               |
| G3452/38 | 8592390388049 | 17,00                 | 1,700               |
| G3452/39 | 8592390388056 | 17,50                 | 1,750               |
| G3452/40 | 8592390388063 | 18,20                 | 1,820               |
| G3452/41 | 8592390388070 | 18,80                 | 1,880               |
| G3452/42 | 8592390388087 | 19,15                 | 1,915               |
| G3452/43 | 8592390388094 | 20,15                 | 2,015               |
| G3452/44 | 8592390388100 | 20,65                 | 2,065               |
| G3452/45 | 8592390388117 | 21,30                 | 2,130               |
| G3452/46 | 8592390388124 | 21,95                 | 2,195               |
| G3452/47 | 8592390388131 | 22,65                 | 2,265               |
| G3452/48 | 8592390388148 | 23,00                 | 2,300               |



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

