

ARDON® BRICK LOW NEO S3S ESD

SAFETY SHOES



DRY AIR



ESD



WATER
REPELLENT



REFLECTIVE

ARDON® BRICK LOW NEO S3S ESD

SAFETY SHOES

ARTICLE

G3458

MATERIAL

Upper
Lining
Sole

WOVEN-TEK- highly resistant fabric, hydrophobic
MESH laminated breathable fabric
PU/rubber, two-component spray coating, oil resistant, anti-static, antislip, resistant up to 300 ° C
glassfiber
kevlar
ANATOMIC HI- POLY FOAM – anatomically shaped EVA foam, absorbs shocks in the heel area

Toe cap
Plate
Insole

SIZE UNIT

38-48
pair

PACKAGE

Units in a carton
Units in a box

10 pairs
1 pair

DIMENSIONS

Carton H x W x D
(cm)
Carton (cbm)

38-39	40-42	43-48
61 x 32 x 38	63,5 x 34 x 40,5	64x 36,5 x 42
0,0742	0,0874	0,0981

Size EUR

Insole length mm

Foot length cm

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
-	-	-	254	260	267	273	280	286	292	299	305	311	318	-	-	-
-	-	-	24,9	25,5	26,2	26,8	27,5	28,1	28,7	29,4	30,0	30,6	31,3	-	-	-

DESCRIPTION

Safety low-cut shoe with an upper made from innovative Woven-Tek material. The upper textile is highly abrasion-resistant, hydrophobic, and offers excellent hygienic properties. The shoe features a PU/rubber injection-molded sole that ensures stability and safety even in demanding terrain. The upper is equipped with a quick-lacing system instead of traditional laces, providing excellent foot protection and stabilization during work. This highly durable model is designed for tough environments and the most demanding work tasks.

NORMS

(EU) 2016/425

EN ISO 20345:2022 Personal protective equipment - Safety footwear

EN IEC 61340-4-3:2018 Electrostatics: Standard test methods for specific application – Footwear

Category S3S FO SR CI HI HRO ESD

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WPA - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
The shoes do not contain metal parts		
HRO - resistance to contact heat up to 300 °C	✓	
HI-insulation of the bottom of the shoe against heat	✓	
CI-insulation of the bottom of the shoe against the cold	✓	
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	
-		
-		
-		



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3458/38	8592390374004	16,4	1,640
G3458/39	8592390374011	16,9	1,690
G3458/40	8592390374028	17,4	1,740
G3458/41	8592390374035	18,3	1,830
G3458/42	8592390374042	18,4	1,840
G3458/43	8592390374059	19,0	1,900
G3458/44	8592390374066	19,4	1,940
G3458/45	8592390374073	19,9	1,990
G3458/46	8592390374080	20,6	2,060
G3458/47	8592390374097	20,8	2,080
G3458/48	8592390374103	21,3	2,130



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

