

## EU Type Examination Certificate

Date: 2023/07/18

n. **860232926/OE**  
rev.03 – 2025/04/09

Validity: 2030/04/08

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: **U-GROUP SRL**  
(Responsible of the PPE) Via Borgomanero, 1 – 28040 Paruzzaro (NO) – Italia

Type of PPE: **Safety footwear** in conformity with **EN ISO 20345:2022 class I** (= footwear made from leather and other materials)

Category of PPE: **II** : "medium" risks.  
This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.

Model **"STOCCOLMA s ESD"**  
code **R111074**

Description:



model: B (ankle boot);  
fastening system: by means of laces;  
processing: direct injection;  
outsole: light grey compact PU "7466 NIC" marked "antistatic oil resistant" (CH00117);  
midsole: black foam PU (CH00117), which also serves as reinforcement of the toe-end;  
upper: black fabric with grey polymeric threads coupled with black felt PUTEK PLUS FF WR FELTRO 350 (SI00678) with heel made of black coated microfiber GORE MATRIX LARICI 2,0 mm (SI00448) with retro-reflective insert LUXOR ARGENTO ECO (SI00245) in the heel area;  
collar: black fabric ALBANY coupled with PE (SI00047);  
tongue: black fabric ALBANY semplice (SI00046), centrally lined and padded;  
bellows: black coated fabric SINTETICO SPICE (SI00002);  
vamp lining: grey three-dimensional knitting coupled with black canvas (SI00743);  
quarter lining: col. 599 grey three-dimensional knitting SURF (SI00468);  
tongue and rear edge lining: red three-dimensional fishnet knitting SURF (SI00469);  
insole: white multi-layered fabric declared conductive, art. "PREMIUM X MXC" by Lenzi (SP00037) or, in alternative, white multi-layered fabric declared conductive, art. "IBISAFE 37RK36KG2" by Biagioli (SP00038) or white multi-layered fabric declared conductive, art. "PS FLEX MXC" by GVT or white multi-layered fabric, art. "H-85" by Ruian Boan-Non Metallic Material Technology, which also serve as perforation resistant inserts;  
removable insock: grey perforated foam material with white central insert in the rear zone, coupled with fluo green fabric with metallic wires and four grey foam outflows in the bending area (TL00162);  
toecap: polymeric material, art. "PS240" by Hawaii (PU00042) or, in alternative, polymeric material, art. "YN522J" by Yunai or polymeric material, art. "XCH522R" by Zhejiang Xincaihong Protective Equipment.

Provided also with optional and interchangeable orthopaedic insocks SECOSOL®, see "Annex 827211301".

Technical Standard: **EN ISO 20344:2021** Personal protective equipment – Test methods for footwear  
**EN ISO 20345:2022** Personal protective equipment – Safety footwear

Intended use: general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.

Size range: from 35 to 48





## EU Type Examination Certificate

Date: 2023/07/18

n. **860232926/OE**

Validity: 2030/04/08

rev.03 – 2025/04/09

Technical File:	<b>DC-20053/E + 19409 + DC-19051 + DC-18612 + DC-16888</b>
Test report:	<b>RCT n°4412059/E + 4351067/E + 4330064/E + 4319048/E + 4252619.01/E</b>
Functions and performance levels:	<p><b>basic requirements for safety footwear (SB)</b> (see Table 2 and 3 of EN ISO 20345:2022): all mandatory ones, among which:</p> <p><b>Slip resistance</b> = on ceramic tile floor with NaLS.</p> <p><b>Additional requirements</b> (Tab. 16 and 20 of EN ISO 20345:2022):  <b>S3S</b> = closed heel area, energy absorption of seat region, antistatic properties, water penetration and absorption, perforation resistance: Type PS, cleated outsole; <b>CI</b> = cold insulation of outsole complex; <b>FO</b> = resistance to fuel oil; <b>SR</b> = slip resistance on ceramic tile floor with glycerine.</p> <p>Note: the footwear also meets the requirement in accordance with IEC 61340-5-1:2016 (IEC 61340-4-3:2017) for the electrical resistance <b>ESD</b> (electric dissipative footwear).  Annex A: Customized occupational footwear – Type 1 (equipped with customized insoles).</p>
Marking:	<p>on a stitched label and displaying the following information:</p> <ul style="list-style-type: none"> <li>- <b>CE Marking</b>;</li> <li>- registered trademark, name and complete address of the Manufacturer;</li> <li>- designation of the footwear (= article name and alphanumeric code);</li> <li>- nr. and year of the Standard of reference + safety symbols;</li> <li>- size of the footwear (printed on the outsole);</li> <li>- production date (month + year);</li> <li>- additional information: website, category of the PPE, "Made in ...".</li> </ul>



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

